

**Air**Start<sup>™</sup>10

# A new beginning in therapy choices

AirStart<sup>™</sup> 10 APAP is ResMed's auto-adjusting positive airway pressure (APAP) therapy device. Part of ResMed Air Solutions, it offers excellent value for those seeking an APAP device that's simple to set up and use.





### Built-in humidification

Heated humidification may help reduce the common side effects of therapy, such as nasal congestion and a dry nose or throat, to deliver even more comfort during the night. Every AirStart 10 therapy device comes with a built-in HumidAir™ humidifier, so your patients can enjoy all the benefits of humidification in one out-of-the-box solution. The humidifier tub is also intuitive to use and manage,

making humidification easy and accessible for more patients.



## Key features

#### Therapy made easy

The AirStart 10 APAP therapy device is designed to be intuitive and easy-to-use. With no complicated menus or settings to navigate, patients can simply plug in the device and press Start.

#### **Excellent value**

With out-of-the-box simplicity, AirStart 10 devices give you excellent value on the latest technology platform.

#### Product codes

AirStart 10 APAP co-pack	37365
HumidAir (cleanable)	37300
SlimLine <sup>™</sup> tubing	36810

## Technical specifications

Operating pressure range	4–20 cm H <sub>2</sub> O
Sound pressure level	26.6 dBA with uncertainty of 2 dBA as measured according to ISO 17510-1:2009 (CPAP mode)
Dimensions (H x W x D)	116 mm x 205 mm x 150 mm
Weight	1106 g
90W power supply unit	Input range 100–240V, 50–60Hz, 57VA (typical power consumption); >108VA (maximum power consumption)
Operating: temperature humidity altitude	+5°C to +35°C 10−95%, non-condensing Sea level to 2,591 m
Storage and transport: temperature humidity	-20°C to +60°C 5–95% relative humidity, non-condensing
Housing construction	Flame retardant engineering thermoplastic
Supplemental oxygen	Recommended maximum flow: 4 L/min
Standard air filter	Polyester non-woven fibre
Tubing	SlimLine (15 mm); Standard (19 mm)
Air outlet	22 mm air outlet complies with ISO 5356-1:2004
Electromagnetic compatibility	Requirements (EMC) according to IEC 60601-1-2: 2007. For residential, commercial, and light industry environments
Aircraft use	ResMed confirms that device meets the Federal Aviation Administration (FAA) requirements (RTCA/DO-160, section 21, category M) for all phases of air travel
IEC 60601-1: 2006 classification	Class II (double insulation), Type BF Ingress protection IP22

